



The compact J6 is the ultimate choice for users who demand the superb stability of Mid-Wheel 6® Design and tight-quarter maneuverability. Highly adaptable, the J6 accepts a wide range of seating and electronics options while its powerful drivetrain delivers high-performance torque.



J6 shown with TRU-Balance®
Tilt and NE+ controller

PRIDE®
PERFORMANCE MOBILITY
— LIVE YOUR BEST™ —

Specifications

DRIVE WHEELS	10"
OMNI-CASTERS	Front: 5" solid Rear: 6" solid
SUSPENSION	ATX Suspension (Active-Trac® with extra stability)
MAXIMUM SPEED ¹	Up to 4 mph
BRAKES	Intelligent braking (electronic, regenerative disc brakes)
GROUND CLEARANCE	2.25"
TURNING RADIUS ²	21.25"
OVERALL SIZE ²	Length: 34.5" Width: 23.25"
SEATING	TRU-Balance® Power Tilt Adjustable Width: 14"-20" Adjustable Depth: 14"-20" Synergy® Seat Adjustable Width: 10"-20" Adjustable Depth: 10"-20" High-back Seat (20" x 20" max. dim.) Medium-back Seat (20" x 20" max. dim.)
DRIVE TRAIN	2-motor, Mid-Wheel 6®
BATTERIES	Two 12 volt, deep cycle U-1
RANGE PER CHARGE ¹	Up to 15 miles
BATTERY CHARGER	5A, off-board
AVAILABLE ELECTRONICS	75A, Q-Logic NE (standard) 75A, Q-Logic NE+ 80A, Q-Logic EX
WEIGHT CAPACITY	300 lbs. maximum (user weight)
BASE WEIGHT	104.5 lbs.
SEAT WEIGHT	42.5 lbs.
BATTERY WEIGHT	24.5 lbs. (each)
WARRANTY	Lifetime limited warranty on frame; 2-year warranty on electronics; 18-month warranty on drive motor

Shroud Colors



Jazzy
Red



Jazzy
Blue



J6 shown with
TRU-Balance®
Tilt and NE+
controller

Features

- Mid-Wheel 6® allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® Tilt ³
- OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters for enhanced performance over more varied terrain
- Easy front access to batteries

Options

- Swing-away joystick mount
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleeves
- Gel adductor buttons
- Power elevating seat
- Angle-adjustable footplates
- 70° swing-away leg rest
- Q-Logic EX Drive Control System

Code Coverage

J6 2S - SS	K0822
J6 2S - C	K0823
J6 2SP - SS	K0835

FOOTNOTES:

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tire pressure.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %. Dimensions shown are for power base only. Overall measurements will vary based on seating and accessory selections.
- 3) 250 lbs. weight capacity

(US) 800-800-8586
(CANADA) 888-570-1113
www.pridemobility.com

Pride®
Mobility Products Corp.
— LIVE YOUR BEST™ —

The information provided at this time is preliminary.